



STATE OF NEVADA  
DIVISION OF MINERALS  
DISSOLVED MINERAL RESOURCE EXPLORATION  
BOREHOLE OR WELL DRILLER'S PLUGGING REPORT  
Please complete this form in its entirety in accordance with NAC 534B

Report#: PB0002  
For Division Use Only

Borehole:   
Well:

PRINT OR TYPE IN BLACK INK ONLY  
DO NOT WRITE ON BACK

1. OPERATOR Bonaventure Nevada Inc.  
MAILING ADDRESS 4235 Christy Way  
Reno, Nevada 89519  
COUNTY Washoe  
BOREHOLE OR WELL NAME: BC#3  
PROJECT NAME: Bonnie Claire  
FEDERAL - BLM NVN# n-94783 3809(NVB0200)

2. LOCATION SE 1/4 of the NW 1/4, Sec 26 T 8 N  S, R 44 E  
Latitude \_\_\_\_\_ or UTM E 498500  NAD83  
Longitude \_\_\_\_\_ or UTM N 4119000  WGS84  
3. NDOM Permit/NOI Number N0002

4. Depth Drilled 1860 Feet EXISTING BOREHOLE OR WELL CONSTRUCTION  
Depth Cased 140 8 5/8 Feet (well only)

5. WATER LEVEL  
Static water level 25 feet below land surface  
Artesian Flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water Temperature \_\_\_\_\_ °F

6. BOREHOLE/WELL PLUGGING MATERIALS  
Material Used neat cement From 0 feet to 140 annular feet  Pumped  Poured  
Material Used abandonite From 20 feet to 1800 feet  Pumped  Poured  
Material Used neat cement From 0 feet to 20 inside casing feet  Pumped  Poured  
Material Used \_\_\_\_\_ From \_\_\_\_\_ feet to \_\_\_\_\_ feet  Pumped  Poured  
Material Used \_\_\_\_\_ From \_\_\_\_\_ feet to \_\_\_\_\_ feet  Pumped  Poured  
Material Used \_\_\_\_\_ From \_\_\_\_\_ feet to \_\_\_\_\_ feet  Pumped  Poured  
Neat Cement Fluid Weight lbs/gal 10lb  
Bentonite Grout 20 % bentonite

NEXT SECTION TO BE COMPLETED IN CASE OF WELL PLUGGING ONLY - FOR BOREHOLES SKIP TO SECTION 8

7. WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no  
If well was not cleaned out to total depth please explain why:  
pulled pvc screen out and tremmied in abandonite. entire holes is thick gooey clay that is swelling shut .

Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no  
If pulled, from: 0 feet to 1800 feet

EXISTING CASING SCHEDULE  
Material Used STEEL Size O.D. 8 5/8 (Inches) Wt/Ft \_\_\_\_\_ (Pounds) Wall Thickness 188 (Inches) From 0 (Feet) To 140 (Feet) left in place  
\_\_\_\_\_ (Inches) \_\_\_\_\_ (Pounds) \_\_\_\_\_ (Inches) \_\_\_\_\_ (Feet) \_\_\_\_\_ (Feet)  
\_\_\_\_\_ (Inches) \_\_\_\_\_ (Pounds) \_\_\_\_\_ (Inches) \_\_\_\_\_ (Feet) \_\_\_\_\_ (Feet)

Existing Perforations:  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet From \_\_\_\_\_ feet to \_\_\_\_\_ feet

8. Additional Notes or Comments  
STEEL CASING WAS SET IN TOP SURFACE TO 140 AND CEMENT WAS PUMPED AROUND ANNULUS TO DEPTH OF 140 FEET DUE TO UNSTABLE NATURE OF TOP.

9. Date Started 5 17 2018 Date Completed 6 22 18

10. DRILLER'S CERTIFICATION  
This borehole or well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
Name harris exploration drilling inc. Contractor  
Address p.o. box 5579 fallon nevada 89407 Contractor  
Phone 7608227886 Contractor  
Nevada contractor's license number issued by the State Contractor's Board 0026000a  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2554 patrick harris  
Signed [Signature]  
Date 9-10-2018 by driller performing actual plugging on site

RECEIVED

SEP 21 2018

DIVISION OF MINERALS