RECEIVED

JUN 2 0 2018

DIVISION OF MINERALS

STATE OF NEVADA **COMMISSION ON MINERAL RESOURCES DIVISION OF MINERALS**

400 W. King Street, Suite 106 Carson City, Nevada 89703 (775) 684-7040 | Fax (775) 684-7052 http://minerals.nv.gov

Date Received	
API Number <u>27-021-900</u>	7/
County Mineral	đ
Permit Number / 47 / FOR DIVISION USE ONLY	
FOR DIVISION USE ONLY	

GEOTHERMAL RESOURCE DEVELOPMENT PERMIT APPLICATION

A CONTRACTOR OF THE PARTY OF TH	ate/Business Name of Mines and Geolog	av				
Street Address	1664 North Virginia Street, University of Nevada, Reno MS 178					
City	Reno	•	State NV	Zip Code	89557	
hereby makes	application for a g	eothermal developme	nt permit, State of N	 levada, Divis	ion of Minerals.	
(If applicant is	a corporation, sho	w state and date of inc	corporation; if a part	nership, list	names of partners.)	
11						
This applicatio	n is for a	Domestic well	Commercia	l well	Industrial well	
Other	, specify:	Observation well	■ Thermal Gr	adient well	Re-entry	
Note: Re-entr	y includes workov	er, deepening, or plugg	ging back operation	S.		
Applicant is:	Land Owner	☐ Lease Holder	,			
Applicant is.	Well Name:	41-1				
	Lease Name/No:	<u> </u>		Split Est	ate? Yes No	
	Land Type:	Federal (BLM, US	SFS, etc.)	Private	State	
Location of We	all·					
	sii. treet:					
	County:					
Commercial and	,	615 1/ 1/ 1/ 1/				
<u>⊬3</u> To:		NE 1/2 of, N				
_	·			34E		
UT	M Northing 42918	354 N; UTM	Easting400727_	E (NAD	083 Datum)	
Cor	unty <u>Mineral</u>					
(If a	applicable, give str	eet address below.)				
Stre	eet:	<u>, </u>			ett.	
City	<i>y</i> :					
Sta	te:			Zip:		

Operator's Name: Nevada Bureau of Mines and Geology					
Address: 1664 North Virginia Street, University of Nevada, Reno MS 178					
City, St Zip: Reno, NV 89557					
Drilling Contractor's Name: USGS Research Drilling Program					
Address: 3595 E Patrick Lane #100					
City, St Zip: Las Vegas Nevada 89120					
Rotary Rig Description: Atlas Copco TH75W 3 Axle Truck Mounted Rig					
Hole Size: 7.5" Casing Size: 2" Weight/Gauge: 40#					
Estimated Well Head Temperature: N/A					
Size of BOP: 2000 psi 3000 psi 5000 psi					
Planned Use of Geothermal Resource:					
500' Max temperature gradient holes. Closed ended casing. Not to be flowed. These holes are for research only.					
Planned Disposal of Spent Geothermal Fluid:					
N/A					
Type and Amount of Bond: Bond to be waived by BLM, N/A					
(Exempt for Domestic Class) USGS accepts plugging responsibility (attached letter)					
Bond Issued by: N/A Serial No. N/A					
The Source of the Proposed Geothermal Resource is:					
Possible hydrothermal activity along a concealed fault(s) on SW side of Gabbs Valley					
(List name of hot spring, geologic formation(s) or other source.)					
Total Depth to be Drilled: 500 feet					
Drilling will Commence On or Before: 5/25/2018					
Signature of Applicant/Agent: Saydur DiOus					
Date: 5/16/2018					

Please attach a detailed drilling program including the following information:

1. Well design schematic; casing and mud programs; potential water supply; drilling rig to be used and pad layout; blow out prevention equipment diagram and testing program; directional drilling information if applicable; map of location and access roads. Additional information may be required upon review.

2. The required fee per NAC 534A 210 or 534A.212.

CONDITIONS OF PERMIT

- 1. All permittees must comply with appropriate sections of the Geothermal Rules and Regulations of the Division of Minerals and with applicable rules and regulations of other local, state, and federal agencies.
- 2. During the drilling of domestic geothermal wells, all water strata above the geothermal horizon being used must be sealed or separated in order to prevent their contents from passing into other strata.
- 3. All fresh water and water of value or possible value for other beneficial uses must be confined to their respective strata and be adequately protected by methods approved by the Division. Precautions must be taken in drilling and abandoning wells to guard against any loss of fresh water from the strata in which it occurs, and the contamination of any fresh water by objectionable water.
- 4. The operator of any well must shut off and exclude all water from any geothermal resource-bearing stratum to the satisfaction of the Division.
- 6. Please send daily drilling reports to : Lowell Price..........<u>lprice@minerals.nv.gov</u> and Linda Wells......lwells@minerals.nv.gov
- 7. Additional Conditions/Comments

5. See attached Conditions of Approval.

A.	The 41-1 Temperature Gradient Well must be plugged and abandoned within two years of the drilling completion
	date.
B.	
C.	

This permit does not extend the permittee the right of ingress and egress on public, private or corporate lands.

The issuance of this permit does not waive the requirements that the permit holder obtain other permits from State, Federal, and local agencies.

PERMIT APPROVAL
Approved 6-20-18 with the conditions noted above.
Permit Number 1471
Administrator

Division of Minerals



STATE OF NEVADA COMMISSION ON MINERAL RESOURCES

DIVISION OF MINERALS

400 W. King Street, Suite 106 Carson City, Nevada 89703 (775) 684-7040 • Fax (775) 684-7052 http://minerals.nv.gov/



RICHARD PERRY Administrator

Las Vegas Office: 2030 E. Flamingo Rd. #220, Las Vegas, NV 89119 Phone: (702) 486-4343; Fax: (702) 486-4345

GEOTHERMAL CONDITIONS OF APPROVAL FOR TEMPERATURE GRADIENT WELL GABBS VALLEY 41-1 DRILLING PERMIT 1471

Submit forms and correspondence to:

Nevada Division of Minerals

400 West King Street

Suite 106

Carson City, NV 89703

Communications with the Division shall be directed to:

Lowell Price, Oil, Gas and Geothermal Program Manager

Office 775-684-7045 Email lprice@minerals.nv.us

Cell 775-721-1774 Fax 775-684-7052

Courtney Brailo, Oil, Gas and Geothermal Program Manager

Office 775-684-7046 Email cbrailo@minerals.nv.us

Cell 775-721-2726 Fax 775-684-7052

Rich Perry, Division Administrator

Office 775-684-7047 Email rmperry@minerals.nv.gov

Cell 775-721-0282 Fax 775-684-7052

Voicemail is available on all cell phones and office phones. Please leave a message if you are unable to speak to someone and we will return your call as quickly as possible.

By provision of the current Memorandum of Understanding between NDOM and BLM, you may contact the following individuals for information or approvals. Approvals under the MOU apply to Fee and Federal lease locations.

John Menghini, Fluid Minerals Team, Petroleum Engineer, Reno

Office 775-861-6573 Email John_Menghini@blm.gov

Cell 775-223-1359 Fax 775-861-6711

YOUR APPLICATION TO DRILL THE GABBS VALLEY 41-1 TEMPERATURE GRADIENT WELL, PERMIT 1470, IS APPROVED SUBJECT TO THE FOLLOWING PERMIT CONDITIONS

- 1. These conditions shall be posted at the well site and read by all company personnel associated with the subject wells.
- 2. The operator shall give notification at least 48 hours prior to spudding. These notifications may be by telephone or email. Please refer to the contacts list on page one of this notice.
- 3. Operator will monitor temperature of mud returns continuously. If temperature exceeds 150 degrees Fahrenheit, drilling operations must cease and the division contacted to review the drilling program. BOPE may be necessary to continue to TD.
- 4. Maintain daily drilling records and submit these to the Division with completion reports. The Completion Report shall include the name of the licensed water well driller and the driller's license number.
- 5. The operator in the event of a serious accident, blow out, oil spill or fire, lightning strike, break, leak, or overflow to notify the Division of Minerals immediately. In the event of a spill of hydrocarbons of 25 gallons or more, you must contact NDEP at 1-888-331-NDEP (6337). You will be advised on clean up and disposal procedures.
- 6. Temperature gradient wells must be plugged and abandoned in accordance with NAC 534A.480 within 2 years of the drilling completion date. Hole must be backfilled with mud, granulated bentonite, or bentonite/cement mix and 50 lineal feet of cement placed to surface. Surface must be restored as near as practicable to its original condition.
- 7. A plugging report must be filed within 30 days of the completion of plugging operations.

SUNDRY NOTICES OIL, GAS AND GEOTHERMAL

Verbal approval for the following work may be given by the Division:

- Any emergency work necessary to prevent or control blow outs or other situations with significant potential to result in injury to the crew or damage to the environment or resource.
- 2. Any kick-offs necessary to by-pass bad hole or fish left in hole.
- 3. Changes in casing points due to bad hole.

- 4. Deepening, attempting to encounter resource.
- 5. Necessary well work to keep geothermal power plants operating.
- 6. Drilling equipment failure.
- 7. Squeeze or plug backs to prevent any injected geothermal or oil field waters from contaminating other water zones.

The operator is required to file a written sundry notice with the division subsequent to verbal approval.

Verbal approvals will not be given for any work that can be planned in advance, such as acidizing, changes in casing points or completion, etc., reentry of a well, remedial work, production or injection testing.