RECEIVED

ILIN 2 0 2022

DIVISION OF MINERALS



STATE OF NEVADA **DIVISION OF MINERALS DISSOLVED MINERAL RESOURCE EXPLORATION BOREHOLE OR WELL DRILLER'S PLUGGING REPORT** Please complete this form in its entirety in

Report#: PW 0002 For Division Use Only

> Borehole: Well

accordance with NAC 534B 1. OPERATOR Lithlum Ore Corp. BOREHOLE OR WELL NAME PROJECT NAME: Railroad Valley Project MAILING ADDRESS 100 Washington Street #100 FEDERAL - BLM NVN# Reno. NV 89503 COUNTY Washoe ON OS. R 3. NDOM Permit/NOI Number 2. LOCATION NE 1/4 of the SW 1/4 Sec 07 57 o NAD83 UTM E 621042E W0006 Latitude 38.56587 WGS84 HTM N Longitude -115.61087 4269520N **EXISTING BOREHOLE OR WELL CONSTRUCTION** Depth Drilled 3000 3000 Feet (well only) **Deoth Cased** Feet WATER LEVEL At surface feet below land surface Static water level G.P.M. P.S.I. Artesian Flow 0 Water Temperature abeint ٩F 6. BOREHOLE/WELL PLUGGING MATERIALS Pumped Poured Material Used Neat Cement From feet to feat Poured Material Used **Neat Cement** feet to 100 feet Pumped From Material Used Pumped Poured **Bentinite Chips** From 100 feet to 110 feet Material Used **Bentitnite Grout** From 3000 feet Pumped Poured 110 feet to Poured Material Used Pumped From feet to feet Material Used From Pumped Poured feet to Neat Cement Fluid Weight lbs/gal 94 bs/5.2 gallons Bentonite Grout 22.8 % bentonite NEXT SECTION TO BE COMPLETED IN CASE OF WELL PLUGGING ONLY - FOR BOREHOLES SKIP TO SECTION 8 Was well cleaned out to total depth? o yes If well was not cleaned out to total depth please explain why: Was the casing pulled? yes o no If pulled, from: feet to Was the casing over drilled? on o Ves **EXISTING CASING SCHEDULE** Wall Thickness WI/Ft Material Used Size O.D. From To 3000 (Feet) (Feet) steel (Inches) (Pounds) 0.312 (Inches) Steel 9.625 (Inches) 40 (Pounds) 0.395 (Inches) 0 (Feet) 615 (Feet) (Inches) (Pounds) (Inches) Steel 14 63.3 .385 Ö (Feet) 70 (Feet) **Existing Perforations:** 2871 1595 From feet to 1840 feet From 2550 feet to feet From 1980 feet to 2100 feet From feet to feel From 2220 feet to 2510 feet From feet to feel 8. Additional Notes or Comments 37 - 94 lbs bags cement used, 198- 50 lbs sacks bore grout used, one plug set, 20 50lbs bags fine bentinete chips used, well ID; 6.366 3.94 bbl/100ft During Orginal Well Construction Well casings cemented in from bottom to top, then perferated

Well Cleaned out then pumped bentitnite surry from the bottom up using 2 3/4 tremmle pipe, plug set at 110 ft and 10ft of bentine fine chips were used. Neat Cement was pumped down on top of plug to 1 ft from surface. After cement had set for 24 hours the top cap of cement was poured 9. Date Started 5-13-2022 Date Completed 5-19-2022 10. DRILLER'S CERTIFICATION This borehole or well was plugged and abandoned under my supervision and the report is true to the best of my knowledge. Name Drittrite LLC Contractor Address 233 Springfeild Pkwy Springcreek, NV 89815 Contractor Phone 775-388-7883 Nevada contractor's license number issued by the State Contractor's Board 0085843 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1533 J2276 Signed by driller performing actual plugging on site

5-28-2022

Date