

RECEIVED

JUL 05 2022



STATE OF NEVADA DIVISION OF MINERALS DISSOLVED MINERAL RESOURCE EXPLORATION BOREHOLE OR WELL DRILLER'S PLUGGING REPORT

Report: PWOODY For Division Use Only

Borehole: [] Well: [x]

PRINT OR TYPE IN BLACK INK ONLY DO NOT WRITE ON BACK

1. OPERATOR GEOXPLOER CORP. MAILING ADDRESS 8-650 CLYDE AVE WEST VANCOUVER, VANCOUVER V7T1E2 COUNTY CANADA BOREHOLE OR WELL NAME: DH-1 PROJECT NAME: ACME DH-1 FEDERAL - BLM NV# 101026

2. LOCATION NW 1/4 of the NE 1/4, Sec 6 T 2 N S, R 40 E 3. NDM Permit/NOI Number W0014 Latitude -117.580231 or UTM E NAD83 Longitude 37.801483 or UTM N WGS84

4. Depth Drilled 1400 Feet EXISTING BOREHOLE OR WELL CONSTRUCTION Depth Cased 202 Feet (well only)

5. WATER LEVEL Static water level 75 feet below land surface Artesian Flow NA G.P.M. NA P.S.J. Water Temperature 70.8 °F

6. BOREHOLE/WELL PLUGGING MATERIALS Material Used Baroid Boregrout From 1400 feet to 30 feet [x] Pumped [] Poured Material Used Portland Cement From 30 feet to SURFACE feet [x] Pumped [x] Poured Material Used From feet to feet [x] Pumped [x] Poured Material Used From feet to feet [x] Pumped [x] Poured Material Used From feet to feet [x] Pumped [x] Poured Material Used From feet to feet [x] Pumped [x] Poured Neat Cement Fluid Weight lbs/gal 15.4 Bentonite Grout 28 SOLIDS % bentonite

NEXT SECTION TO BE COMPLETED IN CASE OF WELL PLUGGING ONLY - FOR BOREHOLES SKIP TO SECTION 8

7. WELL PLUGGING PROCEDURE Was well cleaned out to total depth? [x] yes [] no If well was not cleaned out to total depth please explain why:

After water sampling was complete, 3 inch schedule 80 pvc was removed from hole. Hole was plugged utilizing the HQ drill string from bottom to surface.

Was the casing pulled? [x] yes [] no If pulled, from: 1400 feet to surface feet Was the casing over drilled? [x] yes [] no

EXISTING CASING SCHEDULE Material Used Size O.D. Wt/Ft Wall Thickness From To HWT 4.5 (Inches) 11.7 (Pounds) .50 (Inches) 202 (Feet) surface (Feet)

Existing Perforations From N/A feet to feet From feet to feet From feet to feet

8. Additional Notes or Comments Hole was cored HQ from surface to 202 ft and then reamed to 8 5/8" at which time 4 1/2" HWT casing was set and then cemented in with neat cement utilizing a rubber pump down plug. After abandoning was complete, the HWT surface casing was cutoff below ground level and permanent cap was welded on.

9. Date Started 06-27-2022 Date Completed 06-28-2022

10. DRILLER'S CERTIFICATION

This borehole or well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name Harris Exploration Drilling Contractor

Address PO Box 5579 Fallon, NV 89407 Contractor

Phone 760-822-7886 Contractor

Nevada contractor's license number issued by the State Contractor's Board 0026000A

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1793

Signed [Signature] by driller performing actual plugging on site

Date 07-05-2022