

RECEIVED

AUG 19 2022

DIVISION OF MINERALS



STATE OF NEVADA
DIVISION OF MINERALS
DISSOLVED MINERAL RESOURCE EXPLORATION
BOREHOLE OR WELL DRILLER'S PLUGGING REPORT

Report# For Division Use Only

Borehole: []
Well: []

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

1. OPERATOR Lone Mountain Resources LLC
MAILING ADDRESS 1700, 20th South st
Oakland, CA 94607
COUNTY Alameda

BOREHOLE OR WELL NAME: Alkali Lake Test 1
PROJECT NAME: Alkali Lake
FEDERAL - BLM NWN# 101165

2. LOCATION SW 1/4 of the NW 1/4, Sec 8 T 1 N S. R 41 E
Latitude or UTM E 4191467 NAD83
Longitude or UTM N 464374 WGS84
3. NDOM Permit/NOI Number W0013

4. EXISTING BOREHOLE OR WELL CONSTRUCTION
Depth Drilled 1944 Feet Depth Cased 152 Feet (well only)

5. WATER LEVEL
Static water level 58 feet below land surface
Artesian Flow NA G.P.M. NA P.S.I.
Water Temperature 68 °F

6. BOREHOLE/WELL PLUGGING MATERIALS
Material Used Baroid Bore Grout From 1944 feet to 25 feet [] Pumped [] Poured
Material Used Portland Cement From 25 feet to surface feet [] Pumped [] Poured
Material Used From feet to feet [] Pumped [] Poured
Material Used From feet to feet [] Pumped [] Poured
Material Used From feet to feet [] Pumped [] Poured
Material Used From feet to feet [] Pumped [] Poured
Neat Cement Fluid Weight lbs/gal 15.6
Bentonite Grout 20 solids % bentonite

NEXT SECTION TO BE COMPLETED IN CASE OF WELL PLUGGING ONLY - FOR BOREHOLES SKIP TO SECTION 8

7. WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? [] yes [] no
If well was not cleaned out to total depth please explain why:
After water sampling was complete, 2 7/8 oil tubing was run within 10 ft of bottom and used as treme to plug and abandon.

Was the casing pulled? [] yes [] no If pulled, from: feet to feet
Was the casing over drilled? [] yes [] no

Table with columns: Material Used, Size O.D., Wt, Wall Thickness, From, To. Row 1: casing, 9 5/8 (Inches), 32.30 (Pounds), .312 (Inches), 152 (Feet), surface (Feet)

Existing Perforations:
From NA feet to feet From feet to feet
From feet to feet From feet to feet
From feet to feet From feet to feet

8. Additional Notes or Comments
Hole was drilled 7 7/8 from surface to 152 ft and then reamed to 14 3/4. 9 5/8 casing was set and then cemented in with neat cement utilizing a 1 inch treme line. After abandoning was complete, 9 5/8 surface casing was cut off below ground level and permanent cap was welded on.

9. Date Started 07-29-2022 Date Completed 07-30-2022

10. DRILLER'S CERTIFICATION

This borehole or well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name Harris Exploration Drilling Contractor

Address PO box 5579 Fallon, NV 89407 Contractor

Phone 760-822-7886 Contractor

Nevada contractor's license number issued by the State Contractor's Board 0026000A

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1793 Rick Lewis

Signed [Signature] by driller performing actual plugging on site

Date 08-04-2022