



STATE OF NEVADA
DIVISION OF MINERALS
DISSOLVED MINERAL RESOURCE EXPLORATION
BOREHOLE OR WELL DRILLER'S PLUGGING REPORT
Please complete this form in its entirety in accordance with NAC 534B

Report#: PW0009 For
Division Use Only

Borehole:
Well:

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

1. OPERATOR USHA Resources Ltd
MAILING ADDRESS 1575 KAMLOOPS ST.
VANCOUVER CANADA V5K 3W1
COUNTY _____

BOREHOLE OR WELL NAME: JP-2202 B
PROJECT NAME: JACK POT LAKE
FEDERAL - BLM NVN#: 101748

2. LOCATION NE 1/4 of the SE 1/4, Sec 18 T 17 N S. R 64 E
Latitude _____ or UTM E 69116.25 NAD83
Longitude _____ or UTM N 4,038,321.13 WGS84

3. NDOM Permit/NOI Number
W0016

4. Depth Drilled 1805 Feet EXISTING BOREHOLE OR WELL CONSTRUCTION
Depth Cased _____ Feet (well only)

5. WATER LEVEL
Static water level 110 feet below land surface
Artesian Flow N/A G.P.M. _____ P.S.I.
Water Temperature 67 °F

6. BOREHOLE/WELL PLUGGING MATERIALS
Material Used Boregrout From 1805 feet to 820 feet Pumped Poured
Material Used Neat Cement From 820 feet to SURFACE feet Pumped Poured
Material Used _____ From _____ feet to _____ feet Pumped Poured
Material Used _____ From _____ feet to _____ feet Pumped Poured
Material Used _____ From _____ feet to _____ feet Pumped Poured
Material Used _____ From _____ feet to _____ feet Pumped Poured
Material Used _____ From _____ feet to _____ feet Pumped Poured
Neat Cement Fluid Weight lbs/gal 15.5
Bentonite Grout _____ % bentonite

NEXT SECTION TO BE COMPLETED IN CASE OF WELL PLUGGING ONLY - FOR BOREHOLES SKIP TO SECTION 8

7. WELL PLUGGING PROCEDURE

Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth please explain why:

Was the casing pulled? yes no If pulled, from: 0 feet to 110 feet
Was the casing over drilled? yes no

Material Used		Size O.D.	Wt/Ft	EXISTING CASING SCHEDULE			
		(Inches)	(Pounds)	Wall Thickness	From	To	
		(Inches)	(Pounds)	(Inches)	(Feet)	(Feet)	(Feet)
		(Inches)	(Pounds)	(Inches)	(Feet)	(Feet)	(Feet)

Existing Perforations:
From _____ feet to _____ feet From _____ feet to _____ feet
From _____ feet to _____ feet From _____ feet to _____ feet
From _____ feet to _____ feet From _____ feet to _____ feet

8. Additional Notes or Comments
Over reamed with 8.5 bit core HWT CASING to 100 Feet and
Tried to pull it Separated at 110. Ran Tremmi down to 800 FT
Pumped Neat Cement 820 FT. to SURFACE
 Hole was previously grouted with bore grout from 1805 to 820.

9. Date Started 2-14-2023 Date Completed 6-23-2023

10. DRILLER'S CERTIFICATION

This borehole or well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name Harris Exploration Drilling and ASSOCIATES inc.
Address P.O. Box 5579 FALLON NEVADA 89407
Phone 760 822 7886
Contractor

Nevada contractor's license number issued by the State Contractor's Board 0022600A
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1533

Signed Scott Chitwood
Date 6-24-2023 by driller performing actual plugging on site