

## STATE OF NEVADA DIVISION OF MINERALS DISSOLVED MINERAL RESOURCE EXPLORATION BOREHOLE OR WELL DRILLER'S PLUGGING REPORT Please complete this form in its entirety in

Report#: PB0056
For Division Use Only

Borehole: • Well: •

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

	DO NOT WRITE ON BACK	4.	accordance w	ith NAC 534B						
1.	OPERATOR Zanskar Geotherma	l & Minerals, Inc.				BOREHOL	E OR WELL	NAME: ROS-RC	Li-008	
	MAILING ADDRESS 90 S 400 W Ste 410					PROJECT NAME: Rose of Snowville Mineral Exp.				
	COUNTY Salt Lake City Pershing	, UT 84101				FEDERAL	- BLM NVN#			
_				750	799 0 0			T 0 1100110	3000	
2.	LOCATION SE 1/4 of the SV	N 1/4, Sec 27	T <u>33</u>	Ø N	S, R	33	E	3. NDOM Perm	IVNOI Number	
	Latitude 40.68977	or UTM E		NAD83				N0133		
	Longitude -118.25023	_ UTM N		WGS84						
4.	/// 1		STING BOREHOLE	OR WELL COM			240			
		_ Feet			Depth Case	ed	340	Feet	(well only)	
5.	17	\		RLEVEL						
	Static water level Artesian Flow	/	feet below land sur G.P.M.	face			P.S.I.			
	Water Temperature		_ G.F.W. *F				_ 1.5.1.			
6.	BOREHOLE/WELL PLUGGING MATER	RIAI S								
•	Material Used 8 bass of	From <b>340</b>	feet to	20	feet		Pumped	Poured		
	Material Used Amc Coour	From	feet to		feet		Pumped	Poured		
	Material Used 50	From	feet to		feet		Pumped	Poured Poured		
	Material Used Lange of Material Used Campant	From 20	feet to 50	rface	_feet feet		Pumped Pumped	Poured Poured		
	Material Used 94-#	From	feet to		feet		2 Pumped	D Poured		
	Neat Cement Fluid Weight lbs/gal	15.5			. 1001		a rumpou	2, 00.00		
	Bentonite Grout	% bentonite								
	NEXT SE	ECTION TO BE COMPLETED	IN CASE OF WELL	PLUGGING O	NLY - FOR B	OREHOLE	S SKIP TO SE	CTION 8		
7.			WELL PLUGG	ING PROCEDU	JRE					
	Was well cleaned out to total depth?	b places explain why:	10							
	ii weli was not deaned out to total depti	If well was not cleaned out to total depth please explain why:								
		***************************************						<del> </del>		
	Was the casing pulled?	yes ono		If pulled, fror	n:		feet to		feet	
		yes 🖸 no								
		1405	EXISTING CA	SING SCHEDU			-			
	Material Used Size O.D. (Inch	Wt/Ft nes) (Pounds	Wall Thickness	(Inches)	From	(Feet)	То	Feet)		
	(Inch			(Inches)		(Feet)		Feet)		
	(Inch			(Inches)		(Feet)		Feet)		
	Suisting Reference									
	Existing Perforations: From feet	t to	feet Fro	om		feet to		feet		
	From feel			m		feet to		feet		
	From feet	t to	feet Fro	om		feet to		feet		
8.	Additional Notes or Comments		~-,	h . 1/ :	. W.	1-	1 0 4	. 2110	//	
	Pulled Napipe	removed pli	19. Stip	each 1	n, ruc	k an	dpum	p 590 g	allons	
	Additional Notes or Comments Pulled No pipe, removed plug. Trip back in, Mix and pump 340 gallons of arout slurry. Trip out 34 pieces of NRQ drill rod,									
	of grout slurry. Trip out 34 pieces of NRQ dill NOQ!									
	Mix and pour 20' cement cap									
9.	Date Started 1-30-25			Date Comp	leted -	-30-	-25	_		
10.	, ,, ,,,		DRILLER'S	ERTIFICATIO	N					
ıv.	This borehole or well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.									
	This butching of well mas progged and abandoned and of my superficient and the operational to the book of my information.									
	Name Major Drilling									
	Contractor  Address 2200 S 4000 W, Salt Lake City, UT 84120									
	Address 2200 S 4000 W, Salt Lake City, 01 64120 Contractor									
	Phone 801-974-0645									
	Novada contracted license number includ by the State Contracted Board									
	Nevada contractor's license number issued by the State Contractor's Board									
	Nevada driller's license number issued by the Division of Water Resources, the on-site driller									
	Signed / Syan Kicaporte hydriller performing actual plugging on site									
	Date 1~ 30 - 25	7 by dr	mer performing actua	ıı piugging on s	ite					