



STATE OF NEVADA  
DIVISION OF MINERALS  
DISSOLVED MINERAL RESOURCE EXPLORATION  
BOREHOLE OR WELL DRILLER'S PLUGGING REPORT

Report#: PB0057  
For Division Use Only

Borehole:   
Well:

PRINT OR TYPE IN BLACK INK ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NAC 534B

1. OPERATOR Zanskar Geothermal & Minerals, Inc. BOREHOLE OR WELL NAME: ROS-RCLi-009  
MAILING ADDRESS 90 S 400 W Ste 410 PROJECT NAME: Rose of Snowville Mineral Exp.  
Salt Lake City, UT 84101 FEDERAL - BLM NVN# \_\_\_\_\_  
COUNTY Pershing

2. LOCATION SW 1/4 of the NW 1/4, Sec 27 T 33  N  S, R 33 E 3. NDOM Permit/NOI Number  
Latitude 40.69805 or UTM E  NAD83 NO134  
Longitude -118.25592 or UTM N  WGS84

4. Depth Drilled 500 Feet EXISTING BOREHOLE OR WELL CONSTRUCTION Depth Cased 500 Feet (well only)

5. WATER LEVEL  
Static water level 140 feet below land surface  
Artesian Flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water Temperature \_\_\_\_\_ °F

6. BOREHOLE/WELL PLUGGING MATERIALS  
Material Used 12 bags of AMC grout From 500 feet to 20 feet  Pumped  Poured  
Material Used 50# From \_\_\_\_\_ feet to \_\_\_\_\_ feet  Pumped  Poured  
Material Used 4 bags of Cement From 20 feet to Surface feet  Pumped  Poured  
Material Used 94# From \_\_\_\_\_ feet to \_\_\_\_\_ feet  Pumped  Poured  
Neat Cement Fluid Weight lbs/gal 15.5  
Bentonite Grout \_\_\_\_\_ % bentonite

NEXT SECTION TO BE COMPLETED IN CASE OF WELL PLUGGING ONLY - FOR BOREHOLES SKIP TO SECTION 8

7. WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no  
If well was not cleaned out to total depth please explain why:  
\_\_\_\_\_  
\_\_\_\_\_

Was the casing pulled?  yes  no If pulled, from: \_\_\_\_\_ feet to \_\_\_\_\_ feet  
Was the casing over drilled?  yes  no

EXISTING CASING SCHEDULE

Material Used	Size O.D. (Inches)	Wt (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)

Existing Perforations:  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet From \_\_\_\_\_ feet to \_\_\_\_\_ feet

8. Additional Notes or Comments  
Pulled NRG pipe, removed plug. Trip back in. Mix and pump 500 gallons of grout slurry. Trip out 50 pieces of NRG drill rod. Mix and pour 20' cement cap.

9. Date Started 1-29-25 Date Completed 1-29-25

10. DRILLER'S CERTIFICATION

This borehole or well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
Name Major Drilling Contractor  
Address 2200 S 4000 W, Salt Lake City, UT 84120 Contractor  
Phone 801-974-0645  
Nevada contractor's license number issued by the State Contractor's Board \_\_\_\_\_  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller \_\_\_\_\_  
Signed Ryan Ricaporte by driller performing actual plugging on site  
Date 1-29-25