

STATE OF NEVADA DIVISION OF MINERALS DISSOLVED MINERAL RESOURCE EXPLORATION

Report#: R0069
For Division Use Only

Borehole:
Well:

PRINT OR TYPE IN BLACK INK ONLY DO NOT WRITE ON BACK

BOREHOLE OR WELL DRILLER'S PLUGGING REPORT Please complete this form in its entirety in accordance with NAC 534B

1.	OPERATOR 3PL Operating Inc	BOREHOLE OR WELL NAME: NA 02-34
	MAILING ADDRESS 1802 North Carson St, Ste 154	PROJECT NAME: Railroad Valley FEDERAL - BLM NVN# 100052/NVNV105846786
	Carson City, NV 89701-1238	FEDERAL - DLIM INVINW 100032/INVINV 103840700
Ż.	LOCATION NW 1/4 of the NW 1/4, Sec 34 T 7 N S, R	R 56 E 3. NDOM Permit/NOI Number
	Latitude -115.672850 UTM E 615842.01 NAD83	NO144
	Longitude 38.428106 Or UTM N 4254150.9 WGS84	14.0.1.1
4.	EXISTING BOREHOLE OR WELL CONSTRUCTION	ON
	Depth Drilled 2667.6 Feet Depth Car	sed 70 Feet (well only)
5.	WATER LEVEL	
	Static water level 117 ft before artesian flow feet below land surface Artesian Flow 20 G.P.M. NA	P.S.I.
	Water Temperature 62 °F	
6.	BOREHOLE/WELL PLUGGING MATERIALS	
	Material Used AMC Grout 20 From 2667 feet to 120 feet	Pumped Poured Pumped Poured
	Material Used 3/8 chips From 120 feet to 90 feet Material Used Portland Cement From 90 feet to surface feet	Pumped Poured
	Material Used From feet to feet	Pumped Poured
	Material Used From feet to feet	Pumped Poured
	Material Used From feet to feet	Pumped Poured
	Neat Cement Fluid Weight lbs/gal 14.7 Bentonite Grout 20% solids % bentonite	
	NEXT SECTION TO BE COMPLETED IN CASE OF WELL PLUGGING ONLY - FOR	BOREHOLES SKIP TO SECTION 8
7.	, WELL PLUGGING PROCEDURE	
	Was well cleaned out to total depth?	T.
	If well was not cleaned out to total depth please explain why:	HACO
	<u> </u>	
		-
	Was the casing pulled?	feet to feet
	Was the casing pulled?	leat to leat
	EXISTING CASING SCHEDULE	_
	Material Used Size O.D. Wi/Ft Wall Thickness From PWT 5.5 (Inches) 14.4 (Pounds) .5 (Inches) surface	To (Feet) 70' (Feet)
	(Inches) (Pounds) .5 (Inches)	(Feet) (Feet)
	(Inches) (Pounds) (Inches)	(Feet) (Feet)
	Existing Perforations:	
	From none feet to feet From	feet to feet
	From feet to feet From	feet to feet
	From feet to feet From	feet tofeet
8.	Additional Notes or Comments NATHE OFFICIAL ADDROX 8100 Ft OF PO ANTI rods 1	were dropped. After severa
- /	attempts to fish roas out it was, wish cossful, ar	Illing continued beside the PO
	string to total death. The PQ roof inere growted is	n place, Top of PQ rods
C	at 427 Ft. MYTESIAN Flow was stopped after plug	19/hg.
		V 0
9.		-05-25
10.	DRILLER'S CERTIFICATION	
	This borehole or well was plugged and abandoned under my supervision and the report is true to the best of my known	wledge.
	Name Lewis Drilling LLC/ Dril Core	DECEM
	Contractor	RECEIVED
	Address 2320 Opal Dr Ely, NV 89301 Contractor	
	Phone 775-296-2102	OCT 2 3 2025
	Nevada contractor's license number issued by the State Contractor's Board 0089544/0089491	
	Nevada driller's licinse number issped by the Division of Water Resources, the on-site driller 1793	DIVISION OF MINERALS
	Since Vi Cata	
	Signed by driller performing actual plugging on site	
	Date 10-10-2025	
	· · · · · · · · · · · · · · · · · · ·	