NEVADA II

STATE OF NEVADA DIVISION OF MINERALS

Report #: R0018

DISSOLVED MINERAL RESOURCE EXPLORATION WELL DRILLER'S REPORT

Please complete this form in its entirety in PRIVATE LEASE ☐ Yes ■ No PRINT OR TYPE IN BLACK INK ONLY accordance with NAC 534B BLM NOTICE NO. NVNV106713113 DO NOT WRITE ON BACK WELL NAME/NUMBER: Norte Geothermal, LLC 701 S Corson St. St. 200. Carson City, NV 69701 HYDROLOGIC BASIN OPERATOR NAME Big Smokey Mineral Exploration MAILING ADDRESS TOI S Carsonst Carson City, NV NAME AND NUMBER: BGS-67(61-32)-29 COUNTY NAD 83 PLSS LOCATION 1/4 Section 29 l,atitude 4214129 ON OS Township 03 Range 40 ☐ WGS 84 Longitude UTM E 455385.6 E RIG TYPE NDOM PERMIT NUMBER **BLOWOUT PREVENTION EQUIPMENT** RVC ☐ Blind Pipe Core □ Rotary ☐ Not Required Annular Type: W0053 Mud Mud Rating: ☐ 2M ☐ 3M **■** 5M O Air Sonic Surface_7* Intermediate Other Size: LITHOLOGIC LOG WELL CONSTRUCTION Depth Cased To: 400 Feet Depth Drilled: 2740 Material Feet Water From To Encountered Circ. Strata HOLE DIAMETER (BIT SIZE) <u>To</u> Alluvium 0 1847 <u>From</u> 1847 1933 9.875 Inches Feet 80 Feet Argillite Inches Feet 400 Feet 80 Granitoid 1933 2073 6.250 Feet Feet 2668.5 2073 2303 3.83 Inches 400 Argillite CASING SCHEDULE Granitoid 2303 2436 Wall Thickness/Grade Marble 2436 Size O.D. Weight/Ft. From To (Inches) (Pounds) (Inches) (Feet) (Feet) 80 7.0 28.4 .328 J55 .251 J55 80 400 11.6 4.5 ANNULAR SEALS Minimum of 50 feet of surface seal and 2 inch annual space required Pumped ☐ Poured Neat Cement to 400 Cement Grout Pumped ☐ Poured to ☐ Poured ☐ Bentonite Grout to ☐ Pumped ☐ Bentonite Chips ☐ Pumped ☐ Poured to ☐ Pumped ☐ Poured Gravel Pack (> 0.2 in.) lo Sand Pack [< 0.2 in.] ☐ Pumped ☐ Poured to Poured Other, explain: ☐ Pumped to PERFORATIONS Type of perforation: 8R-2.5-6-,250 Size of perforation: 8R-2" Length - 6" Center - .250", 10% open area 16 slots/foot Feet To 2688.5 Feet From Feet Feet From Τo From Feet To Feet Feet Date started: 25 From Feet To 8-15 20 Date completed: 20 25 From Feet To Feet 9-2 WATER DATA DRILLER'S CERTIFICATION This well was drilled under my supervision. This report is true to the best of my knowledge. Static water level: Feet below land surface 230 Artesian Flow: N/A G.P.M. N/A P.S.I. Water Max Temperature: ° Fahrenheit Name Major Drilling America 208 Contractor Address 2200 South 4000 West SLC, UT 84120 Contractor DATE RECEIVED: Phone 801-974-0645 Nevada contractor's license number as issued by the State Contractor's Board: Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller) DATE ENTERED: 2653 Signed: FOR DIVISION USE ONLY driller performing actual drilling on site

Date:

DISSOLVED MINERAL RESOURCE EXPLORATION WELL DRILLER'S REPORT